

1" × 17.02 mm

Steel=C45

*Cast iron=G22

16B-1-2-3 25.4 × 17.2mm DIN 8187 ISO/R 606

CHAIN	ISO mm	SPROCKETS	ISO mm
Pitch	25.4	Tooth radius r	26
Internal width	17.02	Radius width C	2.5
Roller Φ	15.88	Tooth width h ₁	16.2
		Tooth width L	15.8
		Tooth width h ₂	47.7
		Tooth width h ₃	79.6

Z	de	dp	TS				TD				TT					
			D	H	for Bush	Type	D	H	for Bush	Type	D	H	for Bush	Type		
13	117.0	106.12	73	38	1615	1										
15	133.0	122.17	78	38	1815	1	-	47.7	2012	3						
17	149.0	138.22	80	32	2012	1	-	47.7	2517	3	-	79.8	2517	5		
19	165.2	154.33	108	45	2517	1	-	47.7	2517	3	-	79.8	3030	5		
21	181.2	170.43	110	45	2517	1	140	51	3020	2	-	79.8	3030	5		
23	197.5	186.53	110	45	2517	1	140	51	3020	2	159	89	3535	4		
25	213.5	202.68	110	45	2517	1	140	51	3020	2	175	89	3535	4		
27	229.8	218.79	110	45	2517	1	140	51	3020	2	175	89	3535	4		
30	254.0	243.00	140	51	3020	1	140	76	3030	2	175	89	3535	4		
38	320.7	307.59	140	51	3020	1	140	76	3030	2	175	89	3535	4		
45	377.1	364.13	140	51	3020	6	140	76	3030	7	215	102	4040	8		
*57	474.0	461.07	140	51	3020	6	175	89	3535	7	215	102	4040	8		
*76	627.0	614.65	140	51	3020	6	175	89	3535	7	215	102	4040	8		
*95	781.1	768.22	140	51	3020	6	215	102	4040	7	215	102	4040	8		
*114	934.3	921.81	140	76	3020	6	215	102	4040	7	260	114	4045	8		

1 1/4" × 3/4"

Steel=C45

*Cast iron=GG22

20B-1-2-3 31.75 × 19.56mm DIN 8187 ISO/R 606

CHAIN	ISO mm	SPROCKETS	ISO mm
Pitch	31.75	Tooth radius r	32
Internal width	19.56	Radius width C	3.5
Roller Φ	19.05	Tooth width h ₁	18.5
		Tooth width L	18.2
		Tooth width h ₂	54.6
		Tooth width h ₃	91

Z	de	dp	TS			
			D	H	for Bush	Type
13	147.6	132.65	90	32	2012	1
15	167.9	152.72	108	45	2517	1
17	187.9	172.78	108	45	2517	1
19	208.1	192.91	108	45	2517	1
21	228.2	213.04	108	45	2517	1
23	248.3	233.17	108	45	2517	1
25	268.5	253.33	108	45	2517	1
27	288.6	273.40	150	51	3020	1
30	318.9	303.75	150	51	3020	1
38	369.6	364.49	160	51	3020	6
*45	470.3	455.17	160	51	3020	6
*57	591.5	576.36	160	51	3020	8
*76	783.5	768.32	160	51	3020	6